

TEKNA

PRESENTS

FLATSPOT®

TEKNA

PRESENTS

FLATSPOT®

TABLE OF CONTENT

PART 1	FLATSPOT FOR PRIVATE BUILDINGS	4
	FLATSPOT 1	6
	FLATSPOT 2	14
	FLATSPOT 3	22
	FLATSPOT 4	24
	FLATSPOT 6	25
	FLATSPOT 7	28
	FLATSPOT 8	31
PART 2	FLATSPOT FOR PUBLIC BUILDINGS	33
	FLATSPOT 1	34
	FLATSPOT 6	39
	FLATSPOT 8	43
	SUMMARY PRICELIST	46 - 49
	GENERAL CONDITIONS	50 - 51

FLATSPOT - Pricelist 2017.01.01.

FLATSPOT DESIGNED AND DEVELOPED BY ERIK HUYSMANS
FLATSPOT IS A REGISTERED TRADEMARK

All prices are unit prices, ex VAT, ex works.
Prices, products and/or parts can be changed without prior notice.

'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for '-CUSTOM' COLOUR* products
less than 20 pieces : € 100,00 NET price.

Each order is subject to and governed solely by the terms and conditions of Tekna (see p. 50 - 51).

TEKNA - Stokkelaar 13, B-9160 Lokeren, Belgium - T. +32 9 348 08 02 - E. sales@tekna.be - www.tekna.be

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.

Citizen LED module 12W - 350mA - **2700K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%.
Power supply LED U > 38V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.01.752-C27	FLATSPOT-1 - LED - BLACK	180,00
500.01.753-C27	FLATSPOT-1 - LED - CHROME	170,00
500.01.754-C27	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.755-C27	FLATSPOT-1 - LED - WHITE	180,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

Citizen LED module 12W - 350mA - **3000K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%.
Power supply LED U > 38V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.01.752-C30	FLATSPOT-1 - LED - BLACK	180,00
500.01.753-C30	FLATSPOT-1 - LED - CHROME	170,00
500.01.754-C30	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.755-C30	FLATSPOT-1 - LED - WHITE	180,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 180mm.

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.01.752-XV2	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XV2	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XV2	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XV2	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.01.752-XV3	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XV3	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XV3	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XV3	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.01.752-XD2	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XD2	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XD2	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XD2	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.01.752-XD3	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XD3	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XD3	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XD3	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 12V LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.

Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm - light distribution 36°.
Power supply 12V.
Use: indoor (IP20).
Energy class A.

500.01.752-S30	FLATSPOT-1 - 12V LED - BLACK	160,00
500.01.753-S30	FLATSPOT-1 - 12V LED - CHROME	150,00
500.01.754-S30	FLATSPOT-1 - 12V LED - GOLD COLOUR	160,00
500.01.755-S30	FLATSPOT-1 - 12V LED - WHITE	160,00
ACCESSORIES AND SPARE PARTS		
350.16.925	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 25°	45,00
350.16.926	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 36°	45,00
350.16.935	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 25°	45,00
350.16.936	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 36°	45,00

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 GU10 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 60°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy class A.

500.01.752-G	FLATSPOT-1 - GU10 LED - BLACK	160,00
500.01.753-G	FLATSPOT-1 - GU10 LED - CHROME	150,00
500.01.754-G	FLATSPOT-1 - GU10 LED - GOLD COLOUR	160,00
500.01.755-G	FLATSPOT-1 - GU10 LED - WHITE	160,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

FLATSPOT-1 GU10 (WITHOUT LAMP)

Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.
Suitable for lamp GU10 230V.
Power supply 230V 50Hz.
Use: indoor (IP20).

500.01.052-G	FLATSPOT-1 - GU10 - BLACK	110,00
500.01.053-G	FLATSPOT-1 - GU10 - CHROME	100,00
500.01.054-G	FLATSPOT-1 - GU10 - GOLD COLOUR	110,00
500.01.055-G	FLATSPOT-1 - GU10 - WHITE	110,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIM VERSION

FLATSPOT-1 TRIM LED DOWNLIGHTER

Application: in case of non leveling ceiling surfaces.
Surface mounted frame possible for all Flatspot built-in.

The surface mounted frame will be painted as follows:
FLATSPOT-1 - WHITE - surface mounted frame WHITE
FLATSPOT-1 - BLACK - surface mounted frame BLACK
FLATSPOT-1 - CHROME - surface mounted frame WHITE
FLATSPOT-1 - GOLD COLOUR- surface mounted GOLD COLOUR
FLATSPOT-1 - WHITE/CHROME - surface mounted frame 'CUSTOM' COLOUR* price on request

FLATSPOT-1 TRIM LED



Semi-recessed downlighter (both for installation in plasterboard as in hard ceiling).
Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 130mm.

Citizen LED module 12W - 350mA - **2700K** - CRI 97 - 1200lm - light distribution 60°.
To connect to external Remote LED driver - dimming down to 20%.
Power supply LED U > 38V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.11.752-C27	FLATSPOT-1 - TRIM - LED - BLACK	200,00
500.11.753-C27	FLATSPOT-1 - TRIM - LED - CHROME	190,00
500.11.754-C27	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	200,00
500.11.755-C27	FLATSPOT-1 - TRIM - LED - WHITE	200,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

Citizen LED module 12W - 350mA - **3000K** - CRI 97 - 1200lm - light distribution 60°.
To connect to external Remote LED driver - dimming down to 20%.
Power supply LED U > 38V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.11.752-C30	FLATSPOT-1 - TRIM - LED - BLACK	200,00
500.11.753-C30	FLATSPOT-1 - TRIM - LED - CHROME	190,00
500.11.754-C30	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	200,00
500.11.755-C30	FLATSPOT-1 - TRIM - LED - WHITE	200,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIM VERSION

FLATSPOT-1 TRIM LED



Semi-recessed downlighter (both for installation in plasterboard as in hard ceiling).
Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 180mm.

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.11.752-XV2	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.753-XV2	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.754-XV2	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.755-XV2	FLATSPOT-1 - TRIM - LED - WHITE	270,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.11.752-XV3	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.753-XV3	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.754-XV3	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.755-XV3	FLATSPOT-1 - TRIM - LED - WHITE	270,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.11.752-XD2	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.753-XD2	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.754-XD2	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.755-XD2	FLATSPOT-1 - TRIM - LED - WHITE	270,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**.
Power supply LED U > 48V DC - I < 350mA.
Use: indoor (IP20).
Energy class A++.

500.11.752-XD3	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.753-XD3	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.754-XD3	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.755-XD3	FLATSPOT-1 - TRIM - LED - WHITE	270,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIM VERSION

FLATSPOT-1 TRIM - 12V LED



Semi-recessed downlighter (both for installation in plasterboard as in hard ceiling).
Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm -
built-in height 130mm.

Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm - light distribution 36°.
Power supply 12V.
Use: indoor (IP20).
Energy class A.

500.11.752-S30	FLATSPOT-1 - TRIM - 12V LED - BLACK	170,00
500.11.753-S30	FLATSPOT-1 - TRIM - 12V LED - CHROME	160,00
500.11.754-S30	FLATSPOT-1 - TRIM - 12V LED - GOLD COLOUR	170,00
500.11.755-S30	FLATSPOT-1 - TRIM - 12V LED - WHITE	170,00

ACCESSORIES AND SPARE PARTS

350.16.925	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 25°	45,00
350.16.926	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 36°	45,00
350.16.935	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 25°	45,00
350.16.936	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 36°	45,00

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIM VERSION

FLATSPOT-1 TRIM GU10 LED



Semi-recessed downlighter (both for installation in plasterboard as in hard ceiling).
Aluminium mirror be at one with the opening.
The mirror is removable.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm -
built-in height 130mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm, light distribution 60°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy class A.

500.11.752-G	FLATSPOT-1 - TRIM - GU10 LED - BLACK	180,00
500.11.753-G	FLATSPOT-1 - TRIM - GU10 LED - CHROME	170,00
500.11.754-G	FLATSPOT-1 - TRIM - GU10 LED - GOLD COLOUR	180,00
500.11.755-G	FLATSPOT-1 - TRIM - GU10 LED - WHITE	180,00

ACCESSORIES AND SPARE PARTS

350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

FLATSPOT-1 TRIM GU10 (WITHOUT LAMP)

Semi-recessed downlighter (both for installation in plasterboard as in hard ceiling).
Aluminium mirror be at one with the opening.
The mirror is removable for lamp replacement.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm -
built-in height 130mm.
Suitable for lamp GU10 230V.
Power supply 230V 50Hz.
Use: indoor (IP20).

500.11.052-G	FLATSPOT-1 - TRIM - GU10 - BLACK	130,00
500.11.053-G	FLATSPOT-1 - TRIM - GU10 - CHROME	120,00
500.11.054-G	FLATSPOT-1 - TRIM - GU10 - GOLD COLOUR	130,00
500.11.055-G	FLATSPOT-1 - TRIM - GU10 - WHITE	130,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.


REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-2 LED



Trimless opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm for plaster ceiling (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.

Citizen LED module 12W - 350mA - **2700K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.02.752-C27	FLATSPOT-2 - LED - BLACK FROSTED GLASS	190,00
500.02.755-C27	FLATSPOT-2 - LED - WHITE FROSTED GLASS	190,00
500.02.75X-C27	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	215,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

Citizen LED module 12W - 350mA - **3000K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.02.752-C30	FLATSPOT-2 - LED - BLACK FROSTED GLASS	190,00
500.02.755-C30	FLATSPOT-2 - LED - WHITE FROSTED GLASS	190,00
500.02.75X-C30	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	215,00

RECOMMENDED LED DRIVER


240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-2 LED



Trimless opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm for plaster ceiling (81mm for concrete ceiling) - outside diameter 80mm - built-in height 180mm.

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.02.752-XV2	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.755-XV2	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.75X-XV2	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.02.752-XV3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.755-XV3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.75X-XV3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.02.752-XD2	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.755-XD2	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.75X-XD2	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.02.752-XD3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.755-XD3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.75X-XD3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00

OPTIONAL


540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-2 - 12V LED



Trimless opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm for plaster ceiling (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.


Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm - light distribution 36°. To connect to external transformer.
Power supply 12V.
Use: indoor and outdoor (IP44).
Energy class A.

500.02.752-S30	FLATSPOT-2 - 12V LED - BLACK FROSTED GLASS	170,00
500.02.755-S30	FLATSPOT-2 - 12V LED - WHITE FROSTED GLASS	170,00
500.02.75X-S30	FLATSPOT-2 - 12V LED - 'CUSTOM' COLOUR* FROSTED GLASS	195,00
ACCESSORIES AND SPARE PARTS		
350.16.925	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 25°	45,00
350.16.926	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 36°	45,00
350.16.935	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 25°	45,00
350.16.936	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 36°	45,00

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-2 GU10 LED



Trimless opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm for plaster ceiling (81mm for concrete ceiling) - outside diameter 80mm - built-in height 106mm.

Soraa lamp LED GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 60°. Power supply 230V 50Hz.
Use: indoor and outdoor (IP44).
Energy class A.

500.02.752-G	FLATSPOT-2 - GU10 LED - BLACK FROSTED GLASS	175,00
500.02.755-G	FLATSPOT-2 - GU10 LED - WHITE FROSTED GLASS	175,00
500.02.75X-G	FLATSPOT-2 - GU10 LED - 'CUSTOM' COLOUR* FROSTED GLASS	200,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

FLATSPOT-2 GU10 (WITHOUT LAMP)

Trimless opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm for plaster ceiling (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.
Suitable for lamp GU10 230V.
Power supply 230V 50Hz.
Use: indoor and outdoor (IP44).

500.02.052-G	FLATSPOT-2 - GU10 - BLACK FROSTED GLASS	125,00
500.02.055-G	FLATSPOT-2 - GU10 - WHITE FROSTED GLASS	125,00
500.02.05X-G	FLATSPOT-2 - GU10 - 'CUSTOM' COLOUR* FROSTED GLASS	150,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIM VERSION

FLATSPOT-2 TRIM DOWNLIGHTER

Application: in case of non leveling ceiling surfaces.
Surface mounted frame possible for all Flatspot built-in.

The surface mounted frame will be painted as follows:
FLATSPOT-2 - WHITE - surface mounted frame WHITE
FLATSPOT-2 - BLACK - surface mounted frame BLACK
FLATSPOT-2 - 'CUSTOM' COLOUR* - surface mounted frame 'CUSTOM' COLOUR*

FLATSPOT-2 TRIM LED



Semi-recessed opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 130mm.

Citizen LED module 12W - 350mA - **2700K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.12.752-C27	FLATSPOT-2 - TRIM - LED - BLACK FROSTED GLASS	210,00
500.12.755-C27	FLATSPOT-2 - TRIM - LED - WHITE FROSTED GLASS	210,00
500.12.75X-C27	FLATSPOT-2 - TRIM - LED - 'CUSTOM' COLOUR* FROSTED GLASS	235,00
RECOMMENDED LED DRIVER		
240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

Citizen LED module 12W - 350mA - **3000K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.12.752-C30	FLATSPOT-2 - TRIM - LED - BLACK FROSTED GLAS	210,00
500.12.755-C30	FLATSPOT-2 - TRIM - LED - WHITE FROSTED GLAS	210,00
500.12.75X-C30	FLATSPOT-2 - TRIM - LED - 'CUSTOM' COLOUR* FROSTED GLAS	235,00
RECOMMENDED LED DRIVER		
240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIM VERSION

FLATSPOT-2 TRIM LED



Semi-recessed opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 180mm.

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.12.752-XV2	FLATSPOT-2 - TRIM - LED - BLACK FROSTED GLASS	280,00
500.12.755-XV2	FLATSPOT-2 - TRIM - LED - WHITE FROSTED GLASS	280,00
500.12.75X-XV2	FLATSPOT-2 - TRIM - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00

OPTIONAL
Bluetooth low energy wireless connectivity 100,00

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.12.752-XV3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	280,00
500.12.755-XV3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	280,00
500.12.75X-XV3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00

OPTIONAL
Bluetooth low energy wireless connectivity 100,00

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.12.752-XD2	FLATSPOT-2 - LED - BLACK FROSTED GLASS	280,00
500.12.755-XD2	FLATSPOT-2 - LED - WHITE FROSTED GLASS	280,00
500.12.75X-XD2	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00

OPTIONAL
Bluetooth low energy wireless connectivity 100,00

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor and outdoor (IP44). Energy class A++.

500.12.752-XD3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	280,00
500.12.755-XD3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	280,00
500.12.75X-XD3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00

OPTIONAL
Bluetooth low energy wireless connectivity 100,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
------	---------------------	----------------------

TRIM VERSION

FLATSPOT-2 TRIM - 12V LED



Semi-recessed opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
 Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 130mm.

Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm - light distribution 36°. To connect to external transformer.
 Power supply 12V.
 Use: indoor and outdoor (IP44).
 Energy class A.

500.12.752-S30	FLATSPOT-2 - TRIM - BLACK FROSTED GLAS	190,00
500.12.755-S30	FLATSPOT-2 - TRIM - WHITE FROSTED GLAS	190,00
500.12.75X-S30	FLATSPOT-2 - TRIM - 'CUSTOM' COLOUR* FROSTED GLAS	215,00
ACCESSORIES AND SPARE PARTS		
350.16.925	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 25°	45,00
350.16.926	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 2700K 465lm 36°	45,00
350.16.935	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 25°	45,00
350.16.936	Soraa lamp LED 12V MR16 GU5,3 CRI 95 9W 3000K 490lm 36°	45,00

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
------	---------------------	----------------------

TRIM VERSION

FLATSPOT-2 TRIM GU10 LED



Semi-recessed opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
 Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 106mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 60°. Power supply 230V 50Hz.
 Use: indoor and outdoor (IP44).
 Energy class A.

500.12.752-G	FLATSPOT-2 - TRIM - GU10 LED - BLACK FROSTED GLAS	195,00
500.12.755-G	FLATSPOT-2 - TRIM - GU10 LED - WHITE FROSTED GLAS	195,00
500.12.75X-G	FLATSPOT-2 - TRIM - GU10 LED - 'CUSTOM' COLOUR* FROSTED GLAS	220,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

FLATSPOT-2 TRIM GU10 (WITHOUT LAMP)

Semi-recessed opal glass. Closing ring with inside frosted Borofloat glass, be at one with the opening.
 Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 89mm - built-in height 106mm.
 Suitable for lamp GU10 230V.
 Power supply 230V 50Hz.
 Use: indoor and outdoor (IP44).

500.12.052-G	FLATSPOT-2 - TRIM - GU10 - BLACK FROSTED GLAS	145,00
500.12.055-G	FLATSPOT-2 - TRIM - GU10 - WHITE FROSTED GLAS	145,00
500.12.05X-G	FLATSPOT-2 - TRIM - GU10 - 'CUSTOM' COLOUR* FROSTED GLAS	170,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
 *'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
 *'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-3



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 82mm.

Philips lamp Aluline B15d 12V 20W 6° clear.
To connect to external transformer.
Power supply 12V.
Use: indoor (IP20).
Energy Class A.

500.03.052	FLATSPOT-3 - BLACK	160,00
500.03.055	FLATSPOT-3 - WHITE	160,00
500.03.05X	FLATSPOT-3 - 'CUSTOM' COLOUR* OPTIONAL	185,00
507.03.052	Screen for FLATSPOT-3 - BLACK	40,00
507.03.055	Screen for FLATSPOT-3 - WHITE	40,00
507.03.05X	Screen for FLATSPOT-3 - 'CUSTOM' COLOUR*	65,00
ACCESSORIES AND SPARE PARTS		
GBD.20.C06	Lamp Philips Aluline B15d 12V 20W 6° clear frontglass CBCP 2000	15,00
GBE.20.C18	Lamp Philips Aluline B15d 12V 20W 18° clear frontglass CBCP 2000	15,00
GBE.20.F18	Lamp Philips Aluline B15d 12V 20W 18° frosted frontglass CBCP 2000	20,00
GBF.20.C32	Lamp Philips Aluline B15d 12V 20W 32° clear frontglass CBCP 2000	15,00
GBF.20.F32	Lamp Philips Aluline B15d 12V 20W 32° frosted frontglass CBCP 2000	20,00
283.70.050	Electronic transformer round 10-50W 230V/12V	25,00
283.PW.060	Electronic transformer 60VA 230V/12V	19,50

FLATSPOT-3 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 82mm.

LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°.
To connect to external driver .
Power supply LED U > 28V DC - I < 250mA.
Use: indoor (IP20).
Energy Class A.

500.03.752	FLATSPOT-3 - LED - BLACK	205,00
500.03.755	FLATSPOT-3 - LED - WHITE	205,00
500.03.75X	FLATSPOT-3 - LED - 'CUSTOM' COLOUR* OPTIONAL	230,00
507.03.052	Screen for FLATSPOT-3 - BLACK	40,00
507.03.055	Screen for FLATSPOT-3 - WHITE	40,00
507.03.05X	Screen for FLATSPOT-3 - 'CUSTOM' COLOUR*	65,00
ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS		
350.SE11.325	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°	60,00
350.SE11.336	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°	60,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

SURFACE MOUNTED

FLATSPOT-3 SURFACE MOUNTED



Adjustable surface mounted downlighter.
Ceiling plate with Spot Optic,
axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 97mm.

Philips lamp Aluline B15d 12V 20W 6° clear.
To connect to external transformer.
Power supply 12V.
Use: indoor (IP20).
Energy Class A.

500.03.952	FLATSPOT-3 - SURFACE MOUNTED - BLACK	160,00
500.03.955	FLATSPOT-3 - SURFACE MOUNTED - WHITE	160,00
500.03.95X	FLATSPOT-3 - SURFACE MOUNTED - 'CUSTOM' COLOUR* OPTIONAL	185,00
507.03.052	Screen for FLATSPOT-3 - BLACK	40,00
507.03.055	Screen for FLATSPOT-3 - WHITE	40,00
507.03.05X	Screen for FLATSPOT-3 - 'CUSTOM' COLOUR*	65,00
ACCESSORIES AND SPARE PARTS		
GBD.20.C06	Lamp Philips Aluline B15d 12V 20W 6° clear frontglass CBCP 2000	15,00
GBE.20.C18	Lamp Philips Aluline B15d 12V 20W 18° clear frontglass CBCP 2000	15,00
GBE.20.F18	Lamp Philips Aluline B15d 12V 20W 18° frosted frontglass CBCP 2000	20,00
GBF.20.C32	Lamp Philips Aluline B15d 12V 20W 32° clear frontglass CBCP 2000	15,00
GBF.20.F32	Lamp Philips Aluline B15d 12V 20W 32° frosted frontglass CBCP 2000	20,00
283.70.050	Electronic transformer round 10-50W 230V/12V	25,00
283.PW.060	Electronic transformer 60VA 230V/12V	19,50

FLATSPOT-3 SURFACE MOUNTED - LED



Adjustable surface mounted downlighter.
Ceiling plate with Spot Optic,
axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 97mm.

LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°.
To connect to external driver .
Power supply LED U > 28V DC - I < 250mA.
Use: indoor (IP20).
Energy Class A.

500.03.9752	FLATSPOT-3 - LED - SURFACE MOUNTED - BLACK	205,00
500.03.9755	FLATSPOT-3 - LED - SURFACE MOUNTED - WHITE	205,00
500.03.975X	FLATSPOT-3 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR* OPTIONAL	230,00
507.03.052	Screen for FLATSPOT-3 - BLACK	40,00
507.03.055	Screen for FLATSPOT-3 - WHITE	40,00
507.03.05X	Screen for FLATSPOT-3 - 'CUSTOM' COLOUR*	65,00
ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS		
350.SE11.325	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°	60,00
350.SE11.336	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°	60,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-4 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 97mm.

LED AR70 B15d 7W 3000K 40° CRI 80 with dimmable driver. (Driver to be mounted external). Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.

500.04.752	FLATSPOT-4 - LED - BLACK	225,00
500.04.755	FLATSPOT-4 - LED - WHITE	225,00
500.04.75X	FLATSPOT-4 - LED - 'CUSTOM' COLOUR*	250,00

ACCESSORIES AND SPARE PARTS

350.26.727	Lamp LED AR70 B15d 7W 40° 2700K - dimmable driver included	65,00
350.26.930	Lamp LED AR70 B15d 7W 40° 3000K - dimmable driver included	65,00

SURFACE MOUNTED

FLATSPOT-4 SURFACE MOUNTED



Adjustable surface mounted downlighter. Ceiling plate with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 97mm.

LED AR70 B15d 7W 3000K 40° CRI 80 with dimmable driver. (Driver to be mounted external). Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.

500.04.952	FLATSPOT-4 - SURFACE MOUNTED - LED - BLACK	225,00
500.04.955	FLATSPOT-4 - SURFACE MOUNTED - LED - WHITE	225,00
500.04.95X	FLATSPOT-4 - SURFACE MOUNTED - LED - 'CUSTOM' COLOUR*	250,00

ACCESSORIES AND SPARE PARTS

350.26.727	Lamp LED AR70 B15d 7W 40° 2700K - dimmable driver included	65,00
350.26.930	Lamp LED AR70 B15d 7W 40° 3000K - dimmable driver included	65,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-6 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 230mm - tube Ø 55mm - tube height 157mm.

LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 28V DC - I < 400mA. Use: indoor (IP20). Energy Class A.

500.06.752	FLATSPOT-6 - LED - BLACK	240,00
500.06.755	FLATSPOT-6 - LED - WHITE	240,00
500.06.75X	FLATSPOT-6 - LED - 'CUSTOM' COLOUR*	270,00

ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS

350.SE16.310	LED module Soraa SLE16 Vivid CRI 95 8,1W 3000K 460lm 10°	75,00
350.SE16.325	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°	75,00
350.SE16.336	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 36°	75,00
240.36.361	SOLoDrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLoDrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

FLATSPOT-6 GU10 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 230mm - tube Ø 55mm - tube height 157mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°. Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.

500.06.752-G	FLATSPOT-6 - GU10 LED - BLACK	210,00
500.06.755-G	FLATSPOT-6 - GU10 LED - WHITE	210,00
500.06.75X-G	FLATSPOT-6 - GU10 LED - 'CUSTOM' COLOUR*	240,00

ACCESSORIES AND SPARE PARTS

350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

SURFACE MOUNTED

FLATSPOT-6 LED SURFACE MOUNTED



Adjustable surface mounted downlighter.
Ceiling plate with Spot Optic,
axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum
height 260mm - tube Ø 55mm - tube height 157mm.

LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°.
To connect to external Remote LED driver - dimming down to 20%.
Power supply LED U > 28V DC - I < 400mA.
Use: indoor (IP20).
Energy Class A.

500.06.9752	FLATSPOT-6 - LED - SURFACE MOUNTED - BLACK	240,00
500.06.9755	FLATSPOT-6 - LED - SURFACE MOUNTED - WHITE	240,00
500.06.975X	FLATSPOT-6 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	270,00
ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS		
350.SE16.310	LED module Soraa SLE16 Vivid CRI 95 8,1W 3000K 460lm 10°	75,00
350.SE16.325	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°	75,00
350.SE16.336	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 36°	75,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

FLATSPOT-6 GU10 LED SURFACE MOUNTED



Adjustable surface mounted downlighter.
Ceiling plate with Spot Optic,
axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate
Ø 75mm - height ceiling plate 15mm - maximum height 260mm - tube Ø 55mm - tube
height 157mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy Class A.

500.06.9752-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - BLACK	210,00
500.06.9755-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - WHITE	210,00
500.06.975X-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	240,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

FOR EUTRAC

FLATSPOT-6 GU10 LED FOR EUTRAC



Adjustable downlighter and adaptor for Eutrac.
Ceiling plate with Spot Optic,
axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: tube Ø 55mm - tube height 157mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy Class A.

500.06.752-G-EU	FLATSPOT-6 - GU10 LED - EU - BLACK	210,00
500.06.755-G-EU	FLATSPOT-6 - GU10 LED - EU - WHITE	210,00
500.06.75X-G-EU	FLATSPOT-6 - GU10 LED - EU - 'CUSTOM' COLOUR*	240,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-7



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 205mm - tube Ø 40mm - tube height 130mm.

Lamp Philips Aluline B15d 12V 20W 6° clear.
To connect to external transformer .
Power supply 12V.
Use: indoor (IP20).
Energy Class A.

500.07.052	FLATSPOT-7 - BLACK	170,00
500.07.055	FLATSPOT-7 - WHITE	170,00
500.07.05X	FLATSPOT-7 - 'CUSTOM' COLOUR*	195,00
ACCESSORIES AND SPARE PARTS		
GBD.20.C06	Lamp Philips Aluline B15d 12V 20W 6° clear frontglass CBCP 2000	15,00
GBE.20.C18	Lamp Philips Aluline B15d 12V 20W 18° clear frontglass CBCP 2000	15,00
GBE.20.F18	Lamp Philips Aluline B15d 12V 20W 18° frosted frontglass CBCP 2000	20,00
GBF.20.C32	Lamp Philips Aluline B15d 12V 20W 32° clear frontglass CBCP 2000	15,00
GBF.20.F32	Lamp Philips Aluline B15d 12V 20W 32° frosted frontglass CBCP 2000	20,00
283.PW.060	Electronic transformer 60VA 230V/12V	19,50

FLATSPOT-7 - LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - maximum height 205mm - tube Ø 40mm - tube height 130mm.

LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°. To connect to external Remote LED driver .
Power supply LED U > 28V DC - I < 250mA.
Use: indoor (IP20).
Energy Class A.

500.07.752	FLATSPOT-7 - LED - BLACK	215,00
500.07.755	FLATSPOT-7 - LED - WHITE	215,00
500.07.75X	FLATSPOT-7 - LED - 'CUSTOM' COLOUR*	240,00
ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS		
350.SE11.325	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°	60,00
350.SE11.336	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°	60,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

SURFACE MOUNTED

FLATSPOT-7 SURFACE MOUNTED



Adjustable surface mounted downlighter.
Ceiling plate with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 235mm - tube Ø 40mm - tube height 130mm.

Lamp Philips Aluline B15d 12V 20W 6° clear.
To connect to external transformer .
Power supply 12V.
Use: indoor (IP20).
Energy Class A.

500.07.952	FLATSPOT-7 - SURFACE MOUNTED - BLACK	170,00
500.07.955	FLATSPOT-7 - SURFACE MOUNTED - WHITE	170,00
500.07.95X	FLATSPOT-7 - SURFACE MOUNTED - 'CUSTOM' COLOUR*	195,00
ACCESSORIES AND SPARE PARTS		
GBD.20.C06	Lamp Philips Aluline B15d 12V 20W 6° clear frontglass CBCP 2000	15,00
GBE.20.C18	Lamp Philips Aluline B15d 12V 20W 18° clear frontglass CBCP 2000	15,00
GBE.20.F18	Lamp Philips Aluline B15d 12V 20W 18° frosted frontglass CBCP 2000	20,00
GBF.20.C32	Lamp Philips Aluline B15d 12V 20W 32° clear frontglass CBCP 2000	15,00
GBF.20.F32	Lamp Philips Aluline B15d 12V 20W 32° frosted frontglass CBCP 2000	20,00
283.PW.060	Electronic transformer 60VA 230V/12V	19,50

FLATSPOT-7 SURFACE MOUNTED - LED



Adjustable surface mounted downlighter.
Ceiling plate with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 235mm - tube Ø 40mm - tube height 130mm.

LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°. To connect to external Remote LED driver .
Power supply LED U > 28V DC - I < 250mA.
Use: indoor (IP20).
Energy Class A.

500.07.9752	FLATSPOT-7 - LED - SURFACE MOUNTED - BLACK	215,00
500.07.9755	FLATSPOT-7 - LED - SURFACE MOUNTED - WHITE	215,00
500.07.975X	FLATSPOT-7 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	240,00
ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS		
350.SE11.325	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°	60,00
350.SE11.336	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°	60,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

FOR EUTRAC

FLATSPOT-7 FOR EUTRAC



Adjustable downlighter with transformer box and adaptor for Eutrac. Complete with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: transformer box length 175mm - width 34mm - height 35mm - tube Ø 40mm - tube height 130mm.

Lamp Philips Aluline B15d 12V 20W 6° clear. With integrated electronic transformer 12V/230V 60VA. Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.

500.07.052-EU	FLATSPOT-7 - EU - BLACK	240,00
500.07.055-EU	FLATSPOT-7 - EU - WHITE	240,00
500.07.05X-EU	FLATSPOT-7 - EU - 'CUSTOM' COLOUR*	270,00
ACCESSORIES AND SPARE PARTS		
GBD.20.C06	Lamp Philips Aluline B15d 12V 20W 6° clear frontglass CBCP 2000	15,00
GBE.20.C18	Lamp Philips Aluline B15d 12V 20W 18° clear frontglass CBCP 2000	15,00
GBE.20.F18	Lamp Philips Aluline B15d 12V 20W 18° frosted frontglass CBCP 2000	20,00
GBF.20.C32	Lamp Philips Aluline B15d 12V 20W 32° clear frontglass CBCP 2000	15,00
GBF.20.F32	Lamp Philips Aluline B15d 12V 20W 32° frosted frontglass CBCP 2000	20,00
283.PW.060	Electronic transformer 60VA 230V/12V	19,50

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-8 GU10 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Tube with visible GU10 Lamp, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - tube Ø 34,5mm - tube height 57mm - height lamp inclusive 94mm maximum.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°. Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.

500.08.752-G	FLATSPOT-8 - GU10 LED - BLACK	175,00
500.08.755-G	FLATSPOT-8 - GU10 LED - WHITE	175,00
500.08.75X-G	FLATSPOT-8 - GU10 LED - 'CUSTOM' COLOUR*	195,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

SURFACE MOUNTED

FLATSPOT-8 GU10 LED SURFACE MOUNTED



Adjustable surface mounted downlighter. Ceiling plate with tube and visible GU10 lamp, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - tube Ø 34,5mm - tube height 57mm - height lamp inclusive 121mm maximum.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°. Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.

500.08.9752-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - BLACK	175,00
500.08.9755-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - WHITE	175,00
500.08.975X-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	195,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
<u>VOOR EUTRAC</u>		
FLATSPOT-8 GU10 LED FOR EUTRAC		
	Adjustable downlighter with adaptor for Eutrac. Tube with visible GU10 lamp, axial adjustable from 0° to 60° directional from 0° to 350°. tube Ø 34,5mm - tube height 57mm - height lamp inclusive 121mm maximum.	
	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°. Power supply 230V 50Hz. Use: indoor (IP20). Energy Class A.	
500.08.752-EU	FLATSPOT-8 - GU10 LED - EU - BLACK	175,00
500.08.755-EU	FLATSPOT-8 - GU10 LED - EU - WHITE	175,00
500.08.75X-EU	FLATSPOT-8 - GU10 LED - EU - 'CUSTOM' COLOUR*	195,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening. The mirror is removable. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.

Citizen LED module 12W - 350mA - **2700K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-C27	FLATSPOT-1 - LED - BLACK	180,00
500.01.753-C27	FLATSPOT-1 - LED - CHROME	170,00
500.01.754-C27	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.755-C27	FLATSPOT-1 - LED - WHITE	180,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

Citizen LED module 12W - 350mA - **3000K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-C30	FLATSPOT-1 - LED - BLACK	180,00
500.01.753-C30	FLATSPOT-1 - LED - CHROME	170,00
500.01.754-C30	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.755-C30	FLATSPOT-1 - LED - WHITE	180,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

Citizen LED module 12W - 350mA - **4000K** - CRI 97 - 1200lm - light distribution 60°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 38V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-C40	FLATSPOT-1 - LED - BLACK	180,00
500.01.753-C40	FLATSPOT-1 - LED - CHROME	170,00
500.01.754-C40	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.755-C40	FLATSPOT-1 - LED - WHITE	180,00

RECOMMENDED LED DRIVER

240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening. The mirror is removable. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 180mm.

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-XV2	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XV2	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XV2	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XV2	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-XV3	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XV3	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XV3	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XV3	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **4000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 1% in **1-10V**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-XV4	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XV4	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XV4	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XV4	FLATSPOT-1 - LED - WHITE	250,00

OPTIONAL

540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
------------	--	--------

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening. The mirror is removable. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 180mm.

Xicato Artist LED module with integrated driver - 12W - 350mA - **2700K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-XD2	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XD2	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XD2	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XD2	FLATSPOT-1 - LED - WHITE	250,00

540.XI.BLE	OPTIONAL Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **3000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-XD3	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XD3	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XD3	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XD3	FLATSPOT-1 - LED - WHITE	250,00

540.XI.BLE	OPTIONAL Bluetooth low energy wireless connectivity	100,00
------------	--	--------

Xicato Artist LED module with integrated driver - 12W - 350mA - **4000K** - CRI 98 - 700lm - light distribution 60° - dimming down to 0,1% in **DALI**. Power supply LED U > 48V DC - I < 350mA. Use: indoor (IP20). Energy class A++.

500.01.752-XD4	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-XD4	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-XD4	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-XD4	FLATSPOT-1 - LED - WHITE	250,00

540.XI.BLE	OPTIONAL Bluetooth low energy wireless connectivity	100,00
------------	--	--------

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 CDM

Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening. The mirror is removable. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 130mm.

Lamp CDM-Rm Mini Elite GX10 20W - 35W of 50W with ballast - not dimmable. Power supply 230V 50Hz. Use: indoor (IP20). Energy class A.

500.01.153-35	FLATSPOT-1 CDM-Rm Mini 35W - CHROME	245,00
500.01.155-35	FLATSPOT-1 CDM-Rm Mini 35W - WHITE	255,00
500.01.153-50	FLATSPOT-1 CDM-Rm Mini 50W - CHROME	245,00
500.01.155-50	FLATSPOT-1 CDM-Rm Mini 50W - WHITE	255,00

ACCESSORIES AND SPARE PARTS

350.35.932	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 25°	45,00
350.35.934	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 40°	45,00
350.50.932	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 25°	45,00
350.50.934	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 40°	45,00
350.50.936	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 60°	45,00
220.35.000	Philips electronic ballast HID PV m 1x35s	50,00
220.50.000	Philips electronic ballast HID PV m 1x50s	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.
*custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-1 GU10 LED



Trimless recessed downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening. The mirror is removable for lamp replacement. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 106mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 60°. Power supply 230V 50Hz. Use: indoor (IP20). Energy class A.

500.01.752-G	FLATSPOT-1 - GU10 LED - BLACK	160,00
500.01.753-G	FLATSPOT-1 - GU10 LED - CHROME	150,00
500.01.754-G	FLATSPOT-1 - GU10 LED - GOLD COLOUR	160,00
500.01.755-G	FLATSPOT-1 - GU10 LED - WHITE	160,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.93.045	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.93.046	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.93.040	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

FLATSPOT-1 GU10 (WITHOUT LAMP)

Trimless downlighter (both for installation in plasterboard as in hard ceiling). Aluminium mirror be at one with the opening. The mirror is removable for lamp replacement. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 106mm. Suitable for lamp GU10 230V. Power supply 230V 50Hz. Use: indoor (IP20).

500.01.052-G	FLATSPOT-1 - GU10 - BLACK	110,00
500.01.053-G	FLATSPOT-1 - GU10 - CHROME	100,00
500.01.054-G	FLATSPOT-1 - GU10 - GOLD COLOUR	110,00
500.01.055-G	FLATSPOT-1 - GU10 - WHITE	110,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-6 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 62mm - maximum height 230mm - tube Ø 55mm - tube height 157mm.

LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°. To connect to external Remote LED driver - dimming down to 20%. Power supply LED U > 28V DC - I < 400mA. Use: indoor (IP20). Energy class A.

500.06.752	FLATSPOT-6 - LED - BLACK	240,00
500.06.755	FLATSPOT-6 - LED - WHITE	240,00
500.06.75X	FLATSPOT-6 - LED - 'CUSTOM' COLOUR*	270,00

ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS

350.SE16.310	LED module Soraa SLE16 Vivid CRI 95 8,1W 3000K 460lm 10°	75,00
350.SE16.325	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°	75,00
350.SE16.336	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 36°	75,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

FLATSPOT-6 GU10 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 62mm - maximum height 230mm - tube Ø 55mm - tube height 157mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°. Power supply LED U > 28V DC - I < 400mA. Use: indoor (IP20). Energy class A.

500.06.752-G	FLATSPOT-6 - GU10 LED - BLACK	210,00
500.06.755-G	FLATSPOT-6 - GU10 LED - WHITE	210,00
500.06.75X-G	FLATSPOT-6 - GU10 LED - 'CUSTOM' COLOUR*	240,00

ACCESSORIES AND SPARE PARTS

350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.93.045	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.93.046	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.93.040	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour: prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces: € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERION

FLATSPOT- 6 CDM



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Visible deep-set tube, be at one with the ceiling edge, complete with Optic-Spot, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 62mm - maximum height 230mm - tube Ø 55mm - tube height 157mm.

Lamp CDM-Rm Mini Elite GX10 35W of 50W with ballast - not dimmable. (Ballast to be mounted external). Main power 230V 50Hz. Energy class A.

500.06.152-35	FLATSPOT-6 - CDM-Rm Mini 35W - BLACK	295,00
500.06.155-35	FLATSPOT-6 - CDM-Rm Mini 35W - WHITE	295,00
500.06.15X-35	FLATSPOT-6 - CDM-Rm Mini 35W - 'CUSTOM' COLOUR*	350,00
500.06.152-50	FLATSPOT-6 - CDM-Rm Mini 50W - BLACK	295,00
500.06.155-50	FLATSPOT-6 - CDM-Rm Mini 50W - WHITE	295,00
500.06.15X-50	FLATSPOT-6 - CDM-Rm Mini 50W - 'CUSTOM' COLOUR*	350,00
ACCESSORIES AND SPARE PARTS		
350.35.932	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 25°	45,00
350.35.934	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 40°	45,00
350.50.932	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 25°	45,00
350.50.934	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 40°	45,00
350.50.936	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 60°	45,00
220.35.000	Philips electronic ballast HID PV m 1x35s	50,00
220.50.000	Philips electronic ballast HID PV m 1x50s	50,00

SURFACE MOUNTED

FLATSPOT-6 LED SURFACE MOUNTED



Adjustable surface mounted downlighter. Ceiling plate with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 260mm - tube Ø 55mm - tube height 157mm.

LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°. To connect to external Remote LED driver - dimming down to 20%. Power supply 230V 50Hz. Use: indoor (IP20). Energy class A.

500.06.9752	FLATSPOT-6 - LED - SURFACE MOUNTED - BLACK	240,00
500.06.9755	FLATSPOT-6 - LED - SURFACE MOUNTED - WHITE	240,00
500.06.975X	FLATSPOT-6 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	270,00
ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS		
350.SE16.310	LED module Soraa SLE16 Vivid CRI 95 8,1W 3000K 460lm 10°	75,00
350.SE16.325	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°	75,00
350.SE16.336	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 36°	75,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

SURFACE MOUNTED

FLATSPOT-6 GU10 LED SURFACE MOUNTED



Adjustable surface mounted downlighter. Ceiling plate with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 260mm - tube Ø 55mm - tube height 157mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°. Power supply LED U > 28V DC - I < 400mA. Use: indoor (IP20). Energy class A.

500.06.9752-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - BLACK	210,00
500.06.9755-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - WHITE	210,00
500.06.975X-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	240,00
ACCESSORIES AND SPARE PARTS		
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.93.045	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.93.046	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.93.040	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

FLATSPOT-6 CDM SURFACE MOUNTED



Adjustable surface mounted downlighter. Ceiling plate with Spot Optic, axial adjustable from 0° to 60° - directional from 0° to 350°. Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - maximum height 260mm - tube Ø 55mm - tube height 157mm.

Lamp CDM-Rm Mini Elite GX10 35W of 50W with ballast - not dimmable. (Ballast to be mounted external). Main power 230V 50Hz. Energy class A.

500.06.9152-35	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 35W - BLACK	295,00
500.06.9155-35	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 35W - WHITE	295,00
500.06.915X-35	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 35W - 'CUSTOM' COLOUR*	350,00
500.06.9152-50	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 50W - BLACK	295,00
500.06.9155-50	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 50W - WHITE	295,00
500.06.915X-50	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 50W - 'CUSTOM' COLOUR*	350,00

ACCESSORIES AND SPARE PARTS		
350.35.932	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 25°	45,00
350.35.934	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 40°	45,00
350.50.932	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 25°	45,00
350.50.934	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 40°	45,00
350.50.936	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 60°	45,00
220.35.000	Philips electronic ballast HID PV m 1x35s	50,00
220.50.000	Philips electronic ballast HID PV m 1x50s	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

FOR EUTRAC

FLATSPOT-6 GU10 LED FOR EUTRAC



Adjustable downlighter with driverbox and adaptor for Eutrac.
Complete with Spot Optic, axial adjustable from 0° to 60° directional from 0° to 350°.
Dimensions: tube Ø 55mm - tube height 157mm.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy class A.

500.06.752-G-EU	FLATSPOT-6 - GU10 LED - EU - BLACK	210,00
500.06.755-G-EU	FLATSPOT-6 - GU10 LED - EU - WHITE	210,00
500.06.75X-G-EU	FLATSPOT-6 - GU10 LED - EU - 'CUSTOM' COLOUR*	240,00

ACCESSORIES AND SPARE PARTS

350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.93.045	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.93.046	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.93.040	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

FLATSPOT-6 CDM FOR EUTRAC



Adjustable downlighter with driverbox and adaptor for Eutrac.
Complete with Spot Optic, axial adjustable from 0° to 60° directional from 0° to 350°.
Dimensions: tube Ø 55mm - tube height 157mm.

Lamp CDM-Rm Mini Elite GX10 35W of 50W with ballast - not dimmable.
(Ballast to be mounted external).
Main power 230V 50Hz.
Energy class A.

500.06.152-EU-35	FLATSPOT-6 - EU - CDM-Rm Mini 35W - BLACK	295,00
500.06.155-EU-35	FLATSPOT-6 - EU - CDM-Rm Mini 35W - WHITE	295,00
500.06.15X-EU-35	FLATSPOT-6 - EU - CDM-Rm Mini 35W - 'CUSTOM' COLOUR*	350,00

500.06.152-EU-50	FLATSPOT-6 - EU - CDM-Rm Mini 50W - BLACK	295,00
500.06.155-EU-50	FLATSPOT-6 - EU - CDM-Rm Mini 50W - WHITE	295,00
500.06.15X-EU-50	FLATSPOT-6 - EU - CDM-Rm Mini 50W - 'CUSTOM' COLOUR*	350,00

ACCESSORIES AND SPARE PARTS

350.35.932	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 25°	45,00
350.35.934	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 40°	45,00
350.50.932	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 25°	45,00
350.50.934	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 40°	45,00
350.50.936	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 60°	45,00
220.35.000	Philips electronic ballast HID PV m 1x35s	50,00
220.50.000	Philips electronic ballast HID PV m 1x50s	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE PRODUCT DESCRIPTION UNIT PRICE VAT EXCL.

TRIMLESS VERSION

FLATSPOT-8 GU10 LED



Trimless recessed adjustable downlighter (both for installation in plasterboard as in hard ceiling). Tube with visible GU10 lamp, axial adjustable from 0° to 60° directional from 0° tot 350°.
Dimensions: cut out 83mm (81mm for concrete ceiling) - outside diameter 80mm - built-in height 65mm - tube Ø 34,5mm - tube height 57mm - height inclusive lamp 94mm maximum.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy class A.

500.08.752-G	FLATSPOT-8 - GU10 LED - BLACK	175,00
500.08.755-G	FLATSPOT-8 - GU10 LED - WHITE	175,00
500.08.75X-G	FLATSPOT-8 - GU10 LED - 'CUSTOM' COLOUR*	195,00

ACCESSORIES AND SPARE PARTS


350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.74.010	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 430lm 10°	50,00
350.74.025	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.74.036	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.74.060	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

SURFACE MOUNTED

FLATSPOT-8 GU10 LED SURFACE MOUNTED



Adjustable surface mounted downlighter.
Ceiling plate with tube and visible GU10 Lamp,
axial adjustable from 0° to 60° - directional from 0° to 350°.
Dimensions: ceiling plate Ø 75mm - height ceiling plate 15mm - tube Ø 34,5mm - tube height 57mm - height inclusive lamp 121mm maximum.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°.
Power supply 230V 50Hz.
Use: indoor (IP20).
Energy Class A.

500.08.9752-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - BLACK	175,00
500.08.9755-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - WHITE	175,00
500.08.975X-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	195,00

ACCESSORIES AND SPARE PARTS

350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.74.010	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 430lm 10°	50,00
350.74.025	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.74.036	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.74.060	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
------	---------------------	----------------------

VOOR EUTRAC

FLATSPOT-8 GU10 LED FOR EUTRAC



Adjustable downlighter met adapter FOR EUTRAC.
 Tube with visible GU10 Lamp,
 axial adjustable from 0° to 60° directional from 0° to 350°.
 Dimensions: tube Ø 34,5mm - tube height 57mm -
 height inclusive lamp 121mm maximum.

Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm - light distribution 36°.
 Power supply 230V 50Hz.
 Use: indoor (IP20).
 Energy class A.

500.08.752-EU	FLATSPOT-8 - GU10 LED - EU - BLACK	175,00
500.08.755-EU	FLATSPOT-8 - GU10 LED - EU - WHITE	175,00
500.08.75X-EU	FLATSPOT-8 - GU10 LED - EU - 'CUSTOM' COLOUR*	195,00

ACCESSORIES AND SPARE PARTS

350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00

Soraa lamp GU10 LED Vivid also available in 4000K on request.

350.74.010	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 430lm 10°	50,00
350.74.025	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.74.036	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.74.060	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*'custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

SUMMARY PRICELIST

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
500.01.052-G	FLATSPOT-1 - GU10 - BLACK	110,00
500.01.053-G	FLATSPOT-1 - GU10 - CHROME	100,00
500.01.054-G	FLATSPOT-1 - GU10 - GOLD COLOUR	110,00
500.01.055-G	FLATSPOT-1 - GU10 - WHITE	110,00
500.01.153-35	FLATSPOT-1 CDM-Rm Mini 35W - CHROME	245,00
500.01.153-50	FLATSPOT-1 CDM-Rm Mini 50W - CHROME	245,00
500.01.155-35	FLATSPOT-1 CDM-Rm Mini 35W - WHITE	255,00
500.01.155-50	FLATSPOT-1 CDM-Rm Mini 50W - WHITE	255,00
500.01.752-C27	FLATSPOT-1 - LED - BLACK	180,00
500.01.752-C30	FLATSPOT-1 - LED - BLACK	180,00
500.01.752-C40	FLATSPOT-1 - LED - BLACK	180,00
500.01.752-G	FLATSPOT-1 - GU10 LED - BLACK	160,00
500.01.752-S30	FLATSPOT-1 - 12V LED - BLACK	160,00
500.01.752-XD2	FLATSPOT-1 - LED - BLACK	250,00
500.01.752-XD3	FLATSPOT-1 - LED - BLACK	250,00
500.01.752-XD4	FLATSPOT-1 - LED - BLACK	250,00
500.01.752-XV2	FLATSPOT-1 - LED - BLACK	250,00
500.01.752-XV3	FLATSPOT-1 - LED - BLACK	250,00
500.01.752-XV4	FLATSPOT-1 - LED - BLACK	250,00
500.01.753-C27	FLATSPOT-1 - LED - CHROME	170,00
500.01.753-C30	FLATSPOT-1 - LED - CHROME	170,00
500.01.753-C40	FLATSPOT-1 - LED - CHROME	170,00
500.01.753-G	FLATSPOT-1 - GU10 LED - CHROME	150,00
500.01.753-S30	FLATSPOT-1 - 12V LED - CHROME	150,00
500.01.753-XD2	FLATSPOT-1 - LED - CHROME	240,00
500.01.753-XD3	FLATSPOT-1 - LED - CHROME	240,00
500.01.753-XD4	FLATSPOT-1 - LED - CHROME	240,00
500.01.753-XV2	FLATSPOT-1 - LED - CHROME	240,00
500.01.753-XV3	FLATSPOT-1 - LED - CHROME	240,00
500.01.753-XV4	FLATSPOT-1 - LED - CHROME	240,00
500.01.754-C27	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.754-C30	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.754-C40	FLATSPOT-1 - LED - GOLD COLOUR	180,00
500.01.754-G	FLATSPOT-1 - GU10 LED - GOLD COLOUR	160,00
500.01.754-S30	FLATSPOT-1 - 12V LED - GOLD COLOUR	160,00
500.01.754-XD2	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.754-XD3	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.754-XD4	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.754-XV2	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.754-XV3	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.754-XV4	FLATSPOT-1 - LED - GOLD COLOUR	250,00
500.01.755-C27	FLATSPOT-1 - LED - WHITE	180,00
500.01.755-C30	FLATSPOT-1 - LED - WHITE	180,00
500.01.755-C40	FLATSPOT-1 - LED - WHITE	180,00
500.01.755-G	FLATSPOT-1 - GU10 LED - WHITE	160,00
500.01.755-S30	FLATSPOT-1 - 12V LED - WHITE	160,00
500.01.755-XD2	FLATSPOT-1 - LED - WHITE	250,00
500.01.755-XD3	FLATSPOT-1 - LED - WHITE	250,00
500.01.755-XD4	FLATSPOT-1 - LED - WHITE	250,00
500.01.755-XV2	FLATSPOT-1 - LED - WHITE	250,00
500.01.755-XV3	FLATSPOT-1 - LED - WHITE	250,00
500.01.755-XV4	FLATSPOT-1 - LED - WHITE	250,00
500.02.052-G	FLATSPOT-2 - GU10 - BLACK FROSTED GLASS	125,00
500.02.055-G	FLATSPOT-2 - GU10 - WHITE FROSTED GLASS	125,00
500.02.05X-G	FLATSPOT-2 - GU10 - 'CUSTOM' COLOUR* FROSTED GLASS	150,00
500.02.752-C27	FLATSPOT-2 - LED - BLACK FROSTED GLASS	190,00
500.02.752-C30	FLATSPOT-2 - LED - BLACK FROSTED GLASS	190,00
500.02.752-G	FLATSPOT-2 - GU10 LED - BLACK FROSTED GLASS	175,00
500.02.752-S30	FLATSPOT-2 - 12V LED - BLACK FROSTED GLASS	170,00
500.02.752-XD2	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.752-XD3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.752-XV2	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.752-XV3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	260,00
500.02.755-C27	FLATSPOT-2 - LED - WHITE FROSTED GLASS	190,00
500.02.755-C30	FLATSPOT-2 - LED - WHITE FROSTED GLASS	190,00
500.02.755-G	FLATSPOT-2 - GU10 LED - WHITE FROSTED GLASS	175,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

FLATSPOT pricelist 2017-01-01 - Prices, products and/or parts can be changed without prior notice.
Each order is subject to and governed solely by the terms and conditions of Tekna (see p. 50 - 51).

SUMMARY PRICELIST

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
500.02.755-S30	FLATSPOT-2 - 12V LED - WHITE FROSTED GLASS	170,00
500.02.755-XD2	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.755-XD3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.755-XV2	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.755-XV3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	260,00
500.02.75X-C27	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	215,00
500.02.75X-C30	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	215,00
500.02.75X-G	FLATSPOT-2 - GU10 LED - 'CUSTOM' COLOUR* FROSTED GLASS	200,00
500.02.75X-S30	FLATSPOT-2 - 12V LED - 'CUSTOM' COLOUR* FROSTED GLASS	195,00
500.02.75X-XD2	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00
500.02.75X-XD3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00
500.02.75X-XV2	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00
500.02.75X-XV3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	285,00
500.03.052	FLATSPOT-3 - BLACK	160,00
500.03.055	FLATSPOT-3 - WHITE	160,00
500.03.05X	FLATSPOT-3 - 'CUSTOM' COLOUR*	185,00
500.03.752	FLATSPOT-3 - LED - BLACK	205,00
500.03.755	FLATSPOT-3 - LED - WHITE	205,00
500.03.75X	FLATSPOT-3 - LED - 'CUSTOM' COLOUR*	230,00
500.03.952	FLATSPOT-3 - SURFACE MOUNTED - BLACK	160,00
500.03.955	FLATSPOT-3 - SURFACE MOUNTED - WHITE	160,00
500.03.95X	FLATSPOT-3 - SURFACE MOUNTED - 'CUSTOM' COLOUR*	185,00
500.03.9752	FLATSPOT-3 - LED - SURFACE MOUNTED - BLACK	205,00
500.03.9755	FLATSPOT-3 - LED - SURFACE MOUNTED - WHITE	205,00
500.03.975X	FLATSPOT-3 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	230,00
500.04.752	FLATSPOT-4 - LED - BLACK	225,00
500.04.755	FLATSPOT-4 - LED - WHITE	225,00
500.04.75X	FLATSPOT-4 - LED - 'CUSTOM' COLOUR*	250,00
500.04.952	FLATSPOT-4 - SURFACE MOUNTED - LED - BLACK	225,00
500.04.955	FLATSPOT-4 - SURFACE MOUNTED - LED - WHITE	225,00
500.04.95X	FLATSPOT-4 - SURFACE MOUNTED - LED - 'CUSTOM' COLOUR*	250,00
500.06.152-35	FLATSPOT-6 - CDM-Rm Mini 35W - BLACK	295,00
500.06.152-50	FLATSPOT-6 - CDM-Rm Mini 50W - BLACK	295,00
500.06.152-EU-35	FLATSPOT-6 - EU - CDM-Rm Mini 35W - BLACK	295,00
500.06.152-EU-50	FLATSPOT-6 - EU - CDM-Rm Mini 50W - BLACK	295,00
500.06.155-35	FLATSPOT-6 - CDM-Rm Mini 35W - WHITE	295,00
500.06.155-50	FLATSPOT-6 - CDM-Rm Mini 50W - WHITE	295,00
500.06.155-EU-35	FLATSPOT-6 - EU - CDM-Rm Mini 35W - WHITE	295,00
500.06.155-EU-50	FLATSPOT-6 - EU - CDM-Rm Mini 50W - WHITE	295,00
500.06.15X-35	FLATSPOT-6 - CDM-Rm Mini 35W - 'CUSTOM' COLOUR*	350,00
500.06.15X-50	FLATSPOT-6 - CDM-Rm Mini 50W - 'CUSTOM' COLOUR*	350,00
500.06.15X-EU-35	FLATSPOT-6 - EU - CDM-Rm Mini 35W - 'CUSTOM' COLOUR*	350,00
500.06.15X-EU-50	FLATSPOT-6 - EU - CDM-Rm Mini 50W - 'CUSTOM' COLOUR*	350,00
500.06.752	FLATSPOT-6 - LED - BLACK	240,00
500.06.752-G	FLATSPOT-6 - GU10 LED - BLACK	210,00
500.06.752-G-EU	FLATSPOT-6 - GU10 LED - EU - BLACK	210,00
500.06.755	FLATSPOT-6 - LED - WHITE	240,00
500.06.755-G	FLATSPOT-6 - GU10 LED - WHITE	210,00
500.06.755-G-EU	FLATSPOT-6 - GU10 LED - EU - WHITE	210,00
500.06.75X	FLATSPOT-6 - LED - 'CUSTOM' COLOUR*	270,00
500.06.75X-G	FLATSPOT-6 - GU10 LED - 'CUSTOM' COLOUR*	240,00
500.06.75X-G-EU	FLATSPOT-6 - GU10 LED - EU - 'CUSTOM' COLOUR*	240,00
500.06.9152-35	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 35W - BLACK	295,00
500.06.9152-50	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 50W - BLACK	295,00
500.06.9155-35	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 35W - WHITE	295,00
500.06.9155-50	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 50W - WHITE	295,00
500.06.915X-35	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 35W - 'CUSTOM' COLOUR*	350,00
500.06.915X-50	FLATSPOT-6 - SURFACE MOUNTED - CDM-Rm Mini 50W - 'CUSTOM' COLOUR*	350,00
500.06.9752	FLATSPOT-6 - LED - SURFACE MOUNTED - BLACK	240,00
500.06.9752-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - BLACK	210,00
500.06.9755	FLATSPOT-6 - LED - SURFACE MOUNTED - WHITE	240,00
500.06.9755-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - WHITE	210,00
500.06.975X	FLATSPOT-6 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	270,00
500.06.975X-G	FLATSPOT-6 - GU10 LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	240,00
500.07.052	FLATSPOT-7 - BLACK	170,00
500.07.052-EU	FLATSPOT-7 - EU - BLACK	240,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

FLATSPOT pricelist 2017-01-01 - Prices, products and/or parts can be changed without prior notice.
Each order is subject to and governed solely by the terms and conditions of Tekna (see p. 50 - 51).

SUMMARY PRICELIST

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
500.07.055	FLATSPOT-7 - WHITE	170,00
500.07.055-EU	FLATSPOT-7 - EU - WHITE	240,00
500.07.05X	FLATSPOT-7 - 'CUSTOM' COLOUR*	195,00
500.07.05X-EU	FLATSPOT-7 - EU - 'CUSTOM' COLOUR*	270,00
500.07.752	FLATSPOT-7 - LED - BLACK	215,00
500.07.755	FLATSPOT-7 - LED - WHITE	215,00
500.07.75X	FLATSPOT-7 - LED - 'CUSTOM' COLOUR*	240,00
500.07.952	FLATSPOT-7 - SURFACE MOUNTED - BLACK	170,00
500.07.955	FLATSPOT-7 - SURFACE MOUNTED - WHITE	170,00
500.07.95X	FLATSPOT-7 - SURFACE MOUNTED - 'CUSTOM' COLOUR*	195,00
500.07.9752	FLATSPOT-7 - LED - SURFACE MOUNTED - BLACK	215,00
500.07.9755	FLATSPOT-7 - LED - SURFACE MOUNTED - WHITE	215,00
500.07.975X	FLATSPOT-7 - LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	240,00
500.08.752-EU	FLATSPOT-8 - GU10 LED - EU - BLACK	175,00
500.08.752-G	FLATSPOT-8 - GU10 LED - BLACK	175,00
500.08.755-EU	FLATSPOT-8 - GU10 LED - EU - WHITE	175,00
500.08.755-G	FLATSPOT-8 - GU10 LED - WHITE	175,00
500.08.75X-EU	FLATSPOT-8 - GU10 LED - EU - 'CUSTOM' COLOUR*	195,00
500.08.75X-G	FLATSPOT-8 - GU10 LED - 'CUSTOM' COLOUR*	195,00
500.08.9752-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - BLACK	175,00
500.08.9755-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - WHITE	175,00
500.08.975X-G	FLATSPOT-8 - GU10 LED - SURFACE MOUNTED - 'CUSTOM' COLOUR*	195,00
500.11.052-G	FLATSPOT-1 - TRIM - GU10 - BLACK	130,00
500.11.053-G	FLATSPOT-1 - TRIM - GU10 - CHROME	120,00
500.11.054-G	FLATSPOT-1 - TRIM - GU10 - GOLD COLOUR	130,00
500.11.055-G	FLATSPOT-1 - TRIM - GU10 - WHITE	130,00
500.11.752-C27	FLATSPOT-1 - TRIM - LED - BLACK	200,00
500.11.752-C30	FLATSPOT-1 - TRIM - LED - BLACK	200,00
500.11.752-G	FLATSPOT-1 - TRIM - GU10 LED - BLACK	180,00
500.11.752-S30	FLATSPOT-1 - TRIM - 12V LED - BLACK	170,00
500.11.752-XD2	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.752-XD3	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.752-XV2	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.752-XV3	FLATSPOT-1 - TRIM - LED - BLACK	270,00
500.11.753-C27	FLATSPOT-1 - TRIM - LED - CHROME	190,00
500.11.753-C30	FLATSPOT-1 - TRIM - LED - CHROME	190,00
500.11.753-G	FLATSPOT-1 - TRIM - GU10 LED - CHROME	170,00
500.11.753-S30	FLATSPOT-1 - TRIM - 12V LED - CHROME	160,00
500.11.753-XD2	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.753-XD3	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.753-XV2	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.753-XV3	FLATSPOT-1 - TRIM - LED - CHROME	260,00
500.11.754-C27	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	200,00
500.11.754-C30	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	200,00
500.11.754-G	FLATSPOT-1 - TRIM - GU10 LED - GOLD COLOUR	180,00
500.11.754-S30	FLATSPOT-1 - TRIM - 12V LED - GOLD COLOUR	170,00
500.11.754-XD2	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.754-XD3	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.754-XV2	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.754-XV3	FLATSPOT-1 - TRIM - LED - GOLD COLOUR	270,00
500.11.755-C27	FLATSPOT-1 - TRIM - LED - WHITE	200,00
500.11.755-C30	FLATSPOT-1 - TRIM - LED - WHITE	200,00
500.11.755-G	FLATSPOT-1 - TRIM - GU10 LED - WHITE	180,00
500.11.755-S30	FLATSPOT-1 - TRIM - 12V LED - WHITE	170,00
500.11.755-XD2	FLATSPOT-1 - TRIM - LED - WHITE	270,00
500.11.755-XD3	FLATSPOT-1 - TRIM - LED - WHITE	270,00
500.11.755-XV2	FLATSPOT-1 - TRIM - LED - WHITE	270,00
500.11.755-XV3	FLATSPOT-1 - TRIM - LED - WHITE	270,00
500.12.052-G	FLATSPOT-2 - TRIM - GU10 - BLACK FROSTED GLASS	145,00
500.12.055-G	FLATSPOT-2 - TRIM - GU10 - WHITE FROSTED GLASS	145,00
500.12.05X-G	FLATSPOT-2 - TRIM - GU10 - 'CUSTOM' COLOUR* FROSTED GLASS	170,00
500.12.752-C27	FLATSPOT-2 - TRIM - LED - BLACK FROSTED GLASS	210,00
500.12.752-C30	FLATSPOT-2 - TRIM - LED - BLACK FROSTED GLASS	210,00
500.12.752-G	FLATSPOT-2 - TRIM - GU10 LED - BLACK FROSTED GLASS	195,00
500.12.752-S30	FLATSPOT-2 - TRIM - 12V LED - BLACK FROSTED GLASS	190,00
500.12.752-XD2	FLATSPOT-2 - LED - BLACK FROSTED GLASS	280,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

FLATSPOT pricelist 2017-01-01 - Prices, products and/or parts can be changed without prior notice.
Each order is subject to and governed solely by the terms and conditions of Tekna (see p. 50 - 51).

SUMMARY PRICELIST

CODE	PRODUCT DESCRIPTION	UNIT PRICE VAT EXCL.
500.12.752-XD3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	280,00
500.12.752-XV2	FLATSPOT-2 - TRIM - LED - BLACK FROSTED GLASS	280,00
500.12.752-XV3	FLATSPOT-2 - LED - BLACK FROSTED GLASS	280,00
500.12.755-C27	FLATSPOT-2 - TRIM - LED - WHITE FROSTED GLASS	210,00
500.12.755-C30	FLATSPOT-2 - TRIM - LED - WHITE FROSTED GLASS	210,00
500.12.755-G	FLATSPOT-2 - TRIM - GU10 LED - WHITE FROSTED GLASS	195,00
500.12.755-S30	FLATSPOT-2 - TRIM - 12V LED - WHITE FROSTED GLASS	190,00
500.12.755-XD2	FLATSPOT-2 - LED - WHITE FROSTED GLASS	280,00
500.12.755-XD3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	280,00
500.12.755-XV2	FLATSPOT-2 - TRIM - LED - WHITE FROSTED GLASS	280,00
500.12.755-XV3	FLATSPOT-2 - LED - WHITE FROSTED GLASS	280,00
500.12.75X-C27	FLATSPOT-2 - TRIM - LED - 'CUSTOM' COLOUR* FROSTED GLASS	235,00
500.12.75X-C30	FLATSPOT-2 - TRIM - LED - 'CUSTOM' COLOUR* FROSTED GLASS	235,00
500.12.75X-G	FLATSPOT-2 - TRIM - GU10 LED - 'CUSTOM' COLOUR* FROSTED GLASS	220,00
500.12.75X-S30	FLATSPOT-2 - TRIM - 12V LED - 'CUSTOM' COLOUR* FROSTED GLASS	215,00
500.12.75X-XD2	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00
500.12.75X-XD3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00
500.12.75X-XV2	FLATSPOT-2 - TRIM - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00
500.12.75X-XV3	FLATSPOT-2 - LED - 'CUSTOM' COLOUR* FROSTED GLASS	305,00
507.03.052	Screen for FLATSPOT-3 - BLACK	40,00
507.03.055	Screen for FLATSPOT-3 - WHITE	40,00
507.03.05X	Screen for FLATSPOT-3 'CUSTOM' COLOUR	65,00
	ACCESSORIES, SPARE PARTS AND RECOMMENDED LED DRIVERS	
220.35.000	Philips electronic ballast HID PV m 1x35s	50,00
220.50.000	Philips electronic ballast HID PV m 1x50s	50,00
240.10.300	Lumotech L05011i2 - 20W max. 350/500/700/1200mA 10-24V DC - 180-240V AC	50,00
240.20.350	Lumotech L05011i - 20W max. 350/700/1050mA 10-24V DC - 110V-240V AC	50,00
240.36.361	SOLOdrive 361/A 30W max. 200-1050mA 60V DC max. - 120-250V AC/DC (0-10V)	120,00
240.36.363	SOLOdrive 360/A 30W max. 150-1050mA 60V DC max. - 120-250V AC/DC (Dali)	120,00
283.70.050	Electronic transformer round 10-50W 230V/12V	25,00
283.PW.060	Electronic transformer 60VA 230V/12V	19,50
350.16.925	Soraa lamp LED MR16 12V GU5,3 CRI 95 9W 2700K 465lm 25°	45,00
350.16.926	Soraa lamp LED MR16 12V GU5,3 CRI 95 9W 2700K 465lm 36°	45,00
350.16.935	Soraa lamp LED MR16 12V GU5,3 CRI 95 9W 3000K 490lm 25°	45,00
350.16.936	Soraa lamp LED MR16 12V GU5,3 CRI 95 9W 3000K 490lm 36°	45,00
350.26.727	Lamp LED AR70 B15d 7W 40° 2700K - dimmable driver included	65,00
350.26.930	Lamp LED AR70 B15d 7W 40° 3000K - dimmable driver included	65,00
350.35.932	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 25°	45,00
350.35.934	Lamp Philips CDM-Rm Mini Elite GX10 35W 930 40°	45,00
350.50.932	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 25°	45,00
350.50.934	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 40°	45,00
350.50.936	Lamp Philips CDM-Rm Mini Elite GX10 50W 930 60°	45,00
350.74.010	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 430lm 10°	50,00
350.74.025	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 25°	50,00
350.74.036	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 36°	50,00
350.74.060	Soraa lamp GU10 230V LED Vivid CRI 95 7,5W 4000K 455lm 60°	50,00
350.93.025	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 25°	50,00
350.93.036	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 36°	50,00
350.93.060	Soraa lamp GU10 230V LED Vivid CRI 95 9,5W 3000K 490lm 60°	50,00
350.SE11.325	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 25°	60,00
350.SE11.336	LED module Soraa SLE11 Vivid CRI 95 6,7W 3000K 430lm 36°	60,00
350.SE16.310	LED module Soraa SLE16 Vivid CRI 95 8,1W 3000K 460lm 10°	75,00
350.SE16.325	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 25°	75,00
350.SE16.336	LED module Soraa SLE16 Vivid CRI 95 12,2W 3000K 720lm 36°	75,00
540.XI.BLE	Bluetooth low energy wireless connectivity	100,00
GBD.20.C06	Lamp Philips Aluline B15d 12V 20W 6° clear frontglass CBCP 2000	15,00
GBE.20.C18	Lamp Philips Aluline B15d 12V 20W 18° clear frontglass CBCP 2000	15,00
GBE.20.F18	Lamp Philips Aluline B15d 12V 20W 18° frosted frontglass CBCP 2000	20,00
GBF.20.C32	Lamp Philips Aluline B15d 12V 20W 32° clear frontglass CBCP 2000	15,00
GBF.20.F32	Lamp Philips Aluline B15d 12V 20W 32° frosted frontglass CBCP 2000	20,00

REMARK: In accordance with the EU-norm incandescent and halogen lamps available to exhaustion of stocks.

*custom' colour : prices for minimum quantity of 20 pieces by colour - surcharge for 'custom' colour products less than 20 pieces : € 100,00 NET price.

FLATSPOT pricelist 2017-01-01 - Prices, products and/or parts can be changed without prior notice.
Each order is subject to and governed solely by the terms and conditions of Tekna (see p. 50 - 51).

TEKNA GENERAL CONDITION

Clause 1. Scope of application

Unless otherwise agreed in writing, these general terms and conditions shall apply to each offer of, and each agreement with Tekna, and shall form an integral part of the same. No purchase terms and conditions of the customer shall be binding on Tekna, even if Tekna has not expressly rejected the same. Deviations from these general terms and conditions shall only come into force after Tekna expressly confirms the same in writing.

Clause 2. Offers and acceptance of orders

All price quotations or proposals shall be valid for a period of 14 days and shall be free of any commitment on the part of Tekna. An agreement shall only be formed after the customer accepts the order in writing, and after Tekna also confirms the order placed in writing. Tekna shall also have the right, to be exercised at its discretion, to demand the prior payment of an advance. In such case, a pro forma invoice shall be issued, and the order shall only become definitive after such pro forma invoice is paid in full. Until an offer is accepted, Tekna reserves the right to revoke or alter its offer at any time.

Clause 3. Delivery terms and conditions

The responsibility and the risk relating to the products shall pass to the customer as soon as the agreement is concluded, and insofar as it relates to different types of products, as soon as the same are individually identified. However, the products shall remain the property of Tekna until the time of full payment of the price and related outstandings (see: Clause 11). Unless otherwise agreed to the contrary in writing, Tekna shall always supply the products to the customer on “Ex-Works” (EXW) basis. They shall be transported at the customer’s cost, risk and danger, even if it is agreed that Tekna shall be responsible for transport. The customer is bound, before taking delivery of the products, to inspect them to check the number of units delivered and that they are in a good condition, and also to duly notify the appropriate reservations if any to the carrier. The customer shall also notify remarks if any to Tekna in writing by registered letter, no later than within eight days after delivery.

Clause 4. Execution and delivery periods

The agreed execution or delivery periods are only indicative. These periods shall be respected to the extent possible. If the agreed execution or delivery periods are exceeded however, this fact shall not constitute a ground to terminate the agreement and/or make Tekna liable to pay any damage compensation to the customer. If the customer fails to notify necessary information, or to do so in time, or such information is not consistent with reality, the proposed estimated execution or delivery periods shall be automatically extended by a reasonable period. The same shall apply to changes in the order.

Clause 5. Installation

The products may only be installed by an approved and registered installer. Tekna shall not accept any complaint whatsoever if the customer is unable to prove that the products were installed by an approved and registered installer.

Clause 6. Rejection of products and breach of contract by

customer

If in spite of being served a notice of default, the customer rejects the agreed products, or fails to fulfil its payment obligations, Tekna may, through a registered letter to the customer, terminate the agreement to the detriment of the customer.

If after partial delivery or execution of the contract has already taken place, the customer refuses to accept further delivery or execution, or makes the same impossible, Tekna, provided it sends a registered letter to the customer, may opt to raise an invoice for the executed part of the delivery, and to terminate the agreement by operation of law, to the detriment of the customer, in respect of the part not delivered. Without prejudice to the right of Tekna to demand a higher compensation for the damage that can be proved by it, the customer shall be liable to pay

damage compensation in case of the termination of the agreement, the minimum amount of which, taking into account the potential damage, is fixed at 25% of the price exclusive of VAT on a lump sum basis, or, wherever applicable, the price of the part remaining to be delivered, exclusive of VAT. Advances already paid or additional payments, shall be charged in the following order: 1.) on the damage suffered by Tekna, and 2.) the accrued interest, 3) the costs incurred, and 4.) the invoices still outstanding.

Tekna shall, wherever applicable, have the right to fully or partially suspend the further execution of the related agreement, as well as other agreements for the same customer. The customer shall also be notified concerning the same by registered letter. In case the customer is a consumer, the latter shall have the right to an equivalent compensation if Tekna fails to fulfil its contractual obligations.

Clause 7. Defects and complaints

At the time of delivery, the customer shall immediately examine whether the products delivered contain visible defects or damage, and are in conformity with what was ordered. Problems shall be notified to Tekna, on pain of inadmissibility of the complaint, through registered letter and no later than 8 days after delivery.

Complaints on the grounds of hidden defects shall be notified to Tekna, on pain of inadmissibility of the complaint, through registered letter and no later than 8 days after the discovery of the defect has become possible.

In any case, no complaints shall be accepted if the products delivered have already been processed, incorporated into other products, or resold, or if the products were installed by an unregistered installer without approval.

If a complaint is accepted, the products shall either be repaired or replaced, entirely at the discretion of Tekna. The repair and/or replacement shall never constitute ground for any claim for damage compensation.

No goods may be returned without the written consent of Tekna, and the grant of such consent shall in no case constitute recognition of liability by Tekna. The goods shall be returned at the cost and risk of the customer.

A complaint shall never relieve the customer of the obligation to pay the amounts of the invoices on the dates specified in the agreement, according to the terms and conditions laid down in the agreement. A complaint, even if well-founded, shall also not authorise the customer to refuse to execute the agreement in relation to products that do not form part of the subject of the complaint.

Clause 8. Limitation of liability

For the application of this clause, “indirect damage” shall mean: consequential damage, fire damage, loss of profits, financial or commercial losses, loss of savings, increase in general costs, increased personnel costs, loss of goodwill, damage due to business interruption, damage as a consequence of claims of customers, damage due to disruption of schedules and loss of clientele, etc.

For the application of this clause, “direct damage” shall mean: all the amounts paid to Tekna.

Tekna cannot be held liable for direct or indirect damage, if such damage was caused through external factors or by force majeure (such as for example, storm damage). In addition, Tekna cannot, under any circumstances, be held liable for the oxidation and/or colour change of armatures, if such oxidation and/or colour change is peculiar to the material used. In case of wrong or faulty installation, or installation by an installer without approval, Tekna may not be held liable for possible direct or indirect damage, under any circumstances. Tekna may also not under any circumstances be held liable for any direct or indirect damage in case of wrong use, for example, use in combination with other materials or metals (which may cause electrolysis).

In addition, Tekna may not under any circumstances be held liable for any direct or indirect damage as a consequence of a delivered product if the product was altered or repaired by the customer or by a third party. Except in case of wilful fault or fraud, the total possible liability of Tekna, due to a culpable shortcoming, whether contractual or extra-contractual,

shall in all cases be limited to compensation of the direct damage, subject to a maximum amount of the price (exclusive of VAT) actually invoiced, that is effective for that defective product, multiplied by a factor of 10. In no case shall the total liability of Tekna for direct damage, on any grounds whatsoever, exceed €25,000.00.

The liability of Tekna for indirect damage is expressly excluded. The liability of Tekna due to damage, destruction or loss of data or documents, is also expressly excluded.

If applicable law does not accept the aforesaid limitation of liability, the liability of Tekna shall be limited to the strict minimum permissible under the law.

Liability claims if any of the customer against Tekna shall always have to be filed within one year, counting from the date of delivery of the concerned product that has given rise to the claim. No further liability claim may be made after the expiry of one year.

Clause 9. Intellectual property rights

All intellectual property rights relating to products developed or supplied by Tekna, and related preparatory material or other materials such as analyses, designs, detailed drawings, calculations, illustrations, documentation, reports, offers, models and prototypes shall exclusively belong to Tekna, irrespective of whether these intellectual property rights were registered or filed. Insofar as such right is only acquired through filing, registration or patent, Tekna shall have exclusive right over the same.

Clause 10. Price and payment

Unless otherwise agreed to the contrary in writing, all prices quoted by Tekna are expressed in Euros, and shall apply exclusive of costs, taxes and expenses. The invoices shall be paid in the agreed currency unit.

If due to circumstances beyond the control of Tekna, there is an increase in specific costs that influence the agreed price, for example increases in the duties and taxes on the products to be delivered, increases in freight rates, increases in the prices of basic commodities or raw materials, increases in wages as a consequence of provisions of the law or national or sectoral collective labour agreements, changes in the exchange rate, etc., Tekna shall have the right to charge a proportionate increase after issuing a simple notification.

A deviation from the agreed prices is also possible in the following cases, a non-exhaustive list of which is provided below: (1) where specific factual data provided by the customer no longer correspond to actual reality, (2) in case of material errors, calculation errors or wrong entries in our price calculation, and (3) in case of changes in the initial order.

All invoices shall be payable at the registered office of Tekna. The invoices are payable in cash. All costs shall be borne by the customer. If payment is made by bank transfer, exchange or in any other manner, this cannot be regarded as a waiver of this provision and shall not constitute any novation.

All complaints or remarks concerning an invoice shall be made within 8 days after the invoice date by registered letter with a statement of the reasons for the same, failing which the right to do the same shall lapse. If the faith of Tekna in the creditworthiness of the customer is undermined due to acts of judicial enforcement against the customer and/or there are other demonstrable events that undermine Tekna’s faith that the customer can properly fulfil the commitments undertaken by the customer and/or in case such faith becomes impossible, Tekna reserves the right to cancel the entire order or a part thereof, and to demand appropriate guarantees from the customer. If the customer declines to pursue the same, Tekna reserves to itself the right to cancel the entire order or a part thereof. In that case, the customer shall be bound to pay damage compensation as laid down in Clause 6 of these general terms and conditions.

In case of full or partial non-payment on the due date, interest at the rate of 12% shall be charged on the outstanding invoices, by operation of law and without the need to issue a prior notice of default, and 10% of the invoice amount shall be added to the outstanding balance, subject to a minimum of €125.00 and a maximum of €2,500.00, even if a grace period is allowed.

TEKNA GENERAL CONDITION

In case the customer is a consumer, the latter shall have the right to an equivalent compensation if Tekna fails to fulfil its contractual obligations.

Partial payments shall always be accepted with full reservations and without any prejudicial acknowledgements and shall be applied, in the following order of priority, first to the (judicial) costs incurred, then to the interest that is payable, and then to the damage compensation, and finally to the principal sum. The non-payment of even a single invoice on the due date shall render the outstanding balance on all other invoices, including expired invoices, immediately payable, by operation of law.

Clause 11. Right of retention of title

The products delivered by Tekna to the customer shall remain its property until all the amounts payable by the customer, including interest and costs, are duly paid. As long as the products have not been paid in full, the customer is prohibited to process, sell, to pledge or in any other manner to use the same as security.

Clause 12. Extraneous cause

In case of “extraneous cause” (Section 1147 of the Civil Code) even if it does not lead to permanent and/or absolute impossibility of execution of the contract, Tekna shall have the right, by operation of law, to suspend its obligations or to unilaterally terminate the same after notifying the customer concerning the same. Consequently, Tekna may in no case be bound to pay any damage compensation.

The following, among others, may conventionally be regarded as extraneous causes: war, strike or lockout, exceptional shortages of raw materials or merchandise, weather conditions, fire, natural and/or other disasters, governmental decisions that affect the execution of obligations, insofar as such extraneous cause occurs to the detriment of Tekna or that of our suppliers or co-contractors if any.

Clause 13. Applicable law and jurisdiction clause

The relationship between Tekna and the customer is subject to and shall be construed in accordance with Belgian law, to the exclusion of any other choice of law, and with the exclusion of the Vienna Sales Convention (“United Nations Convention on Contracts for the International Sale of Goods” of 1980). In case of disputes, the Belgian courts of the judicial district of Dendermonde and of the canton of Lokeren shall have exclusive jurisdiction. Tekna shall also have the right to place disputes if any before the court that has jurisdiction as per Section 624 of the Judicial Code.

Clause 14. Independence of the clauses

If it is found that one or more clauses cannot be enforced against the customer in whole or in part, the other provisions contained in the present terms and conditions shall continue in force without any reduction.

