




Electronic Transformers

	Pg
• ET60	247
• ET105	247
• ET150	248
• ET200	248
• ET250	248

Low Voltage Electronic Transformers


Voltage: 240V / 50Hz
 Rated current (Primary): 0.26A
 Secondary voltage (V): 11.65V Max 5.3A AC
 Rated load (W): 20W - 50W
 Short circuit protection - Auto reset on start
 Thermal protection - Single shot
 Surge protection: 1 KVP
 Input terminal: 2.5mm
 Output terminal: 2.5mm
 Dimmable - To be used with a trailing edge dimmer only
 Length: 125mm
 Width: 35mm
 Height: 30mm
 Class: II
 IP: 20
 Code: VIP/TRAY-ET60



ET60

2

Voltage: 240V / 50Hz
 Rated current (Primary): 0.46A
 Secondary voltage (V): 11.5V Max 8.5A AC
 Rated load (W): 35W - 105W
 Short circuit protection - Auto reset on start
 Thermal protection - Single shot
 Surge protection: 1 KVP
 Input terminal: 2.5mm
 Output terminal: 2.5mm
 Dimmable - To be used with a trailing edge dimmer only
 Length: 125mm
 Width: 35mm
 Height: 30mm
 Class: II
 IP: 20
 Code: VIP/TRAY-ET105



ET105

Low Voltage Electronic Transformers


Voltage: 240V / 50Hz
 Rated current (Primary): 0.69A
 Secondary voltage (V): 11.5V Max 12.5A AC
 Rated load (W): 50W - 150W
 Short circuit protection - Auto reset on start
 Thermal protection - Single shot
 Surge protection: 1 KVP
 Input terminal: 2.5mm
 Output terminal: 2.5mm
 Dimmable - To be used with a trailing edge dimmer
 Length: 185mm
 Width: 45mm
 Height: 45mm
 Class: II
 IP: 20
 Code: VIP/TRAY-ET150

ET200

Voltage: 240V / 50Hz
 Rated current (Primary): 0.88A
 Secondary voltage (V): 11.5V Max 16.5A AC
 Rated load (W): 70W - 200W
 Short circuit protection - Auto reset on start
 Thermal protection - Single shot
 Surge protection: 1 KVP
 Input terminal: 2.5mm
 Output terminal: 2.5mm
 Dimmable - To be used with a trailing edge dimmer
 Length: 185mm
 Width: 45mm
 Height: 45mm
 Class: II
 IP: 20
 Code: VIP/TRAY-ET200

ET250

Voltage: 240V / 50Hz
 Rated current (Primary): 1.2A
 Secondary voltage (V): 11.5V Max 20A AC
 Rated load (W): 100W - 250W
 Short circuit protection - Auto reset on start
 Thermal protection - Single shot
 Surge protection: 1 KVP
 Input terminal: 2.5mm
 Output terminal: 2.5mm
 Dimmable - To be used with a trailing edge dimmer
 Length: 185mm
 Width: 45mm
 Height: 45mm
 Class: II
 IP: 20
 Code: VIP/TRAY-ET250



Notes

2



WACO

Industrial Electrical Distributor

249

LIGHTING

